

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number
WO 2004/108610 A1

(51) International Patent Classification⁷: C02F 3/00, (72) Inventor; and
F01D 17/14 (75) Inventor/Applicant (for US only): GRADWELL, Kevan [GB/GB]; 1384 Junction Road West, Lostock, Bolton BL6 4EQ (GB).

(21) International Application Number: PCT/GB2004/001532 (74) Agent: PARKINSON, Neil, Scott; Marks & Clerk, Sussex House, 83-85 Mosley Street, Manchester M2 3LG (GB).

(22) International Filing Date: 7 April 2004 (07.04.2004) (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

(26) Publication Language: English

(30) Priority Data: 0313143.0 7 June 2003 (07.06.2003) GB


(71) Applicant (for all designated States except US): THE BOC GROUP PLC [GB/GB]; Chertsey Road, Windle-sham, Surrey GU20 6HJ (GB).

(71) Applicant (for US only): MANGNALL, Jean (heiress of the deceased inventor) [GB/GB]; 90 St. John's Road, Lo-stock, Bolton BL6 4HA (GB).

(72) Inventor: MANGNAL, Keith (deceased).

[Continued on next page]

(54) Title: COMBINATION OF COMPRESSOR AND PERMANENT MAGNET MOTOR FOR SEWAGE AERATION



(57) Abstract: A sewage aeration turbocompressor for continuously delivering air at a relatively low pressure to a sewage sludge treatment plant. The compressor has a housing, an impeller (10) mounted on an impeller shaft within the housing, and an electric drive motor having an output shaft coupled to and rotating in synchronism with the impeller shaft (9). The housing defines an axial air inlet (4) extending to the impeller, a diffuser passageway (12) extending radially outwards from the impeller, and a volute (13) extending from the diffuser to an air outlet. The electric motor is a variable speed permanent magnetic motor controlled by an inverter and the diffuser is vaneless. High levels of efficiency are achieved over a wide range of impeller speeds, enabling the compressor to deliver large volumes of air across a wide range of delivery rates, by designing the system to deliver optimum efficiency at a relatively low pressure rise less than 1500 millibar.

WO 2004/108610 A1

BEST AVAILABLE COPY



GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

BEST AVAILABLE COPY